



The Power Cord Manufacturer  
www.stayonline.com

**Hubbell Twist-Lock® Devices**  
**30A, 3 Phase 250V AC, 3 Pole, 4 Wire Grounding**  
**Watertight Safety-Shroud® Plug**

**Features**

- Superior cord grip design protects terminations from excess strain.
- Impact resistant shroud protects blades against bending and breaking.
- Reduces exposure to arcing when connecting or disconnecting under load.



**Ordering Information**

Description	Cord Diameter	Hubbell Number
Black PBT housing, white PBT clamps.	.350" - 1.150" (9 - 29 mm)	HBL2721SW

**Stay Online Item # 1861**

**Listings**

Listed to UL 498  
Fed.Spec. W-C-596  
Certified to CSA C22.2 No.42  
UL Listed, CSA Certified to Type 4, 4X and Type 12

**Specifications**

Housing / Cord Clamp	PBT
Terminal Retainer	Clear polycarbonate
Blades	Brass
Terminal Screws	#10-32 Brass (Phillips / Slotted / Robertson)
Terminal Clamp	Cold rolled steel – nickel plated
Assembly Screws	Stainless Steel
Watertight Gland	Neoprene
Closure Plug	Santoprene

**Performance**

**Electrical**

Current Interrupting	Certified for current interrupting at full rated current
Dielect Voltage	Withstands 2,000V minimum

**Mechanical**

Terminal Accommodation	#16 AWG - #8 AWG stranded copper wire only.
Terminal Identification	Terminals identified in accordance with UL 498

**Environmental**

Flammability	V0 per UL94 or CSA 22.2 No.0.17
Moisture Resistance	Type 4, 4X, 12, IP66 suitability
Operating Temperatures	Maximum Continuous 75°C; Minimum -40°C (w/o impact)

