



The Power Cord Manufacturer
www.stayonline.com

Hubbell IEC 309 Pin and Sleeve

60A, 125/250V, 3 Pole, 4 Wire

Watertight Plug

Features

- The solid one-piece pins are machined from solid brass for longer life and reliable electrical contact.
- Watertight neoprene sealing glands provide a reliable seal at the cable entry point. These prevent infiltration of contaminants.
- IEC pin and sleeve devices are color coded by voltage for easy identification.
- Heavy duty external cord grips provide maximum cord retention to maintain secure terminations.

Ordering Information

Description nylon housing, thermoplastic interior

Cord Diameter
.500" - 1.450"
(12.7 - 36.8 mm)

Hubbell Number
HBL460P12W

Stay Online Item # 4043

Listings

Listed to UL Standard
Certified to CSA Standard

Specifications

Device Color	Orange
Housing	Zytel® Nylon
Cord Clamp Material	Reinforced Thermoplastic Polyester
Contact Carrier	High-Impact Thermoset
Terminal Screws	Stainless Steel (300 series)

Performance

Electrical

Current Interrupting	Certified for current interrupting at full rated
Dielect Withstand Voltage	3,000V AC

Mechanical

Terminal Identification	Terminals identified in accordance with North American And IEC conventions.
Product Identification	Identification and ratings are a permanent part of the device housing.

Environmental

Flammability	HB or better per UL 94 or CSA C22.2 No. 0.17
Moisture Resistance	IP67 Suitability
Operating Temperatures	Maximum Continuous +75°C; Minimum -40°C (w/o impact)

