



The Power Cord Manufacturer  
www.stayonline.com

## Hubbell IEC 309 Pin and Sleeve

100A, 3-Phase 120/208V, 4 Pole, 5 Wire

### Watertight Plug

#### Features

- The solid one-piece pins are machined from solid brass for longer life and reliable electrical contact.
- Watertight neoprene sealing glands provide a reliable seal at the cable entry point. These prevent infiltration of contaminants.
- IEC pin and sleeve devices are color coded by voltage for easy identification.
- Heavy duty external cord grips provide minimum cord retention to maintain secure terminations.

#### Ordering Information

Description nylon  
housing,  
thermoplastic  
interior

Cord Diameter  
1.065" - 1.940"  
(27.1 - 49.3 mm)

Hubbell Number  
HBL5100P9W

**Stay Online Item # 4824**

#### Listings

Listed to UL Standard  
Certified to CSA Standard

#### Specifications

Device Color	Blue
Housing	Zytel® Nylon
Cord Clamp Material	Reinforced Thermoplastic Polyester
Contact Carrier	High-Impact Thermoset
Terminal Screws	Stainless Steel (300 series)

#### Performance

##### Electrical

Current Interrupting	Certified for current interrupting at full rated
Dielect Withstand Voltage	3,000V AC

##### Mechanical

Terminal Identification	Terminals identified in accordance with North American And IEC conventions.
Product Identification	Identification and ratings are a permanent part of the device housing.

##### Environmental

Flammability	HB or better per UL 94 or CSA C22.2 No. 0.17
Moisture Resistance	IP67 Suitability
Operating Temperatures	Maximum Continuous +75°C; Minimum -40°C (w/o impact)

